

GS1A THRU GS1M

Features

- For surface mounted application
- Low forward voltage drop
- High current capability
- High reliability
- Classification Rating 94V- 0


Mechanical Data

Case: molded plastic SMA/DO-214AC

Polarity: Color band denotes cathode end

Mounting position: Any

Terminals: Solder plated, solderable per MIL-STD-750,
Method 2026 guaranteed



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load

For capacitive load, derate current by 20%

Type Number	Symbol	GS1A	GS1B	GS1D	GS1G	GS1J	GS1K	GS1M	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current @TL = 100°C	$I_{(AV)}$	1.0							A
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	30							A
Maximum Instantaneous Forward Voltage @ 1.0A	V_F	1.0							V
Maximum DC Reverse Current @ TA=25°C at Rated DC Blocking Voltage @ TA=125°C	I_R	5.0 200							uA
Typical junction capacitance (NOTE 1)	C_j	12							pF
Typical thermal resistance (NOTE 2)	R_{QJA}	57							° C/W
Operating junction and storage temperature range	T_j, T_{STG}	-55 to +150							° C

Note:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Resistance from Junction to Ambient at 0.375(9.5mm) lead length .

Characteristic Curves

